

WAAS CH 48909 W21A	APP CRS 209°	Rwy Idg TDZE 948 Apt Elev 948	5498
--	------------------------	---	-------------



RNAV (GPS) Z RWY 21

GEORGETOWN-SCOTT COUNTY RGNL (27K)

⚠️ **NA** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16° C (4° F) or above 46° C (114° F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Lexington altimeter setting and increase LPV DA to 1186, LNAV/VNAV DA to 1460, and all MDA 40 feet; increase LPV all Cats and LNAV Cats C/D and Circling Cat D visibility ¼ SM. Baro-VNAV and VDP NA with Lexington altimeter setting.

MISSED APPROACH: Climb to 3000 direct YAPUT and right turn on track 301° to SOKOC and right turn on track 049° to GENUS and hold.

AWOS-3 119.975	LEXINGTON APP CON 120.15 259.3 (040° - 220°) 120.75 298.9 (221° - 039°)	CLNC DEL 127.425	UNICOM 123.0 (CTAF) ①
--------------------------	---	----------------------------	---------------------------------



3000	YAPUT	SOKOC	GENUS	4 NM Holding Pattern
↑	✧	✧	△	
	tr 301°		tr 049°	
*LNAV only.				
OBUGE				
CUDIG 1.9 NM to RW21				
ETOXY 2500				
*1.2 NM to RW21				
*1580				
RW21				
1.2 NM 0.7 NM 2.8 NM 6.1 NM				
CATEGORY	A	B	C	D
LPV DA	1148-3/4 200 (200-3/4)			
LNAV/VNAV DA	1422-13/4 474 (500-13/4)			
LNAV MDA	1360-1	412 (500-1)	1360-13/4	412 (500-13/4)
CIRCLING	1420-1	472 (500-1)	1560-13/4 612 (700-13/4)	1660-21/4 712 (800-21/4)