


ASHEVILLE DEP CON ★
124.65 351.8 (Rwy 17)
125.8 269.575 (Rwy 35)
ATLANTA CENTER DEP CON
132.625 353.625 (when twr closed)
ATIS
120.2
GND CON
121.9
ASHEVILLE TOWER ★
121.1 (CTAF) 257.8

TOP ALTITUDE:
8000



TAKEOFF MINIMUMS:
Rwy 17: Standard with minimum climb of 330' per NM to 3600.
Rwy 35: Standard with minimum climb of 490' per NM to 3500.

NOTE: RADAR required.

NOTE: Chart not to scale.

▼	DEPARTURE ROUTE DESCRIPTION
TAKEOFF RUNWAY 17:	Climb on a heading between 147° CW to 187° from DER as assigned by ATC (When tower closed, climb heading 167°) thence. . . .
TAKEOFF RUNWAY 35:	Climb on a heading between 332° CW to 002° from DER as assigned by ATC (When tower closed, climb heading 347°) thence. . . .
. . . .	On RADAR vectors to intercept filed route/fix. Maintain 8000 or lower filed altitude. Expect filed altitude/flight level within 10 minutes after departure.

SE-2, 22 FEB 2024 to 21 MAR 2024

SE-2, 22 FEB 2024 to 21 MAR 2024