

VORTAC DBQ	APP CRS	Rwy Idg	6502
115.8	138°	TDZE	1077
Chan 105		Apt Elev	1077

VOR RWY 13

DUBUQUE RGNL (DBQ)

Inop table does not apply to Cat C. If local altimeter setting not received, use Monticello altimeter setting and increase all MDAs 100 feet. VDP NA when using Monticello altimeter setting.

MALS

MISSED APPROACH: Climb to 2500 then climbing left turn to 3300 via DBQ VORTAC R-112 to SAVAN INT/13 DME and hold.

ATIS 127.25	CHICAGO CENTER 133.95 281.4	DUBUQUE TOWER★ 119.5 (CTAF) 254.4	GND CON 121.8	UNICOM 122.95
----------------	--------------------------------	--------------------------------------	------------------	------------------

ELEV 1077 TDZE 1077

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 44).			
Remain within 10 NM			
DBQ VORTAC 2500 3300 SAVAN DBQ R-112 1880 when using Monticello altimeter setting.			
318° 138° 1780 3.03° TCH 50 0.8 NM 1.3 NM 0.6			
CATEGORY	A	B	C
S-13	1780-3/4 703 (800-3/4)		1780-2 703 (800-2)
CIRCLING	1780-1 703 (800-1)		1800-2 723 (800-2 1/4)
TAYOD FIX MINIMUMS			
S-13	1520-3/4 443 (500-3/4)	1520-1 1/4 443 (500-1 1/4)	1520-1 1/2 443 (500-1 1/2)
CIRCLING	1580-1 503 (600-1)	1600-1 1/2 523 (600-1 1/2)	1800-2 1/4 723 (800-2 1/4)

DUBUQUE, IOWA
Amdt 10A 10OCT19

42°24'N-90°43'W

DUBUQUE RGNL (DBQ)
VOR RWY 13