


WAAS CH 97710 W23A	APP CRS 234°	Rwy Idg TDZE 889 Apt Elev 926
--	------------------------	---


RNAV (GPS) RWY 23L

PIEDMONT TRIAD INTL (GSO)

RNP APCH - GPS.	Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.	ALSf-2 	MISSED APPROACH: Climb to 3000 direct COSIS and hold.
-----------------	--	------------	---

D-ATIS 128.55	GREENSBORO APP CON 124.35 269.225 (250°-049°) 126.6 327.075 (050°-249°)	GREENSBORO TOWER 119.1 290.325	GND CON 121.9 348.6	CLNC DEL 121.75
-------------------------	---	--	-------------------------------	---------------------------



3000	COSIS	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 55).		4 NM Holding Pattern	
					
CATEGORY		A	B	C	D
LPV DA		1089/18		200 (200-½)	
LNAV/ VNAV	DA	1283/35		394 (400-¾)	
LNAV MDA		1280/24 391 (400-½)		1280/35 391 (400-¾)	
 CIRCLING		1440-1 514 (600-1)		1700-2¼ 774 (800-2¼)	1700-2½ 774 (800-2½)

