

WAAS
CH **61221**
W13A

APP CRS
133°

Rwy Idg
TDZE **125**

Apt Elev
125

RNAV (GPS) RWY 13

LUMBERTON RGNL (LBT')


▼

⚠

Rwy 13 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Maxton altimeter setting; increase all MDAs 60 feet; increase LP Cat C and Circling Cat C visibility ¼ SM and LNAV Cat C ½ SM. Straight-in Rwy 13 NA at night, Circling Rwy 13, 31 NA at night.

MISSED APPROACH:
Climb to 3000 direct
NECIR and on track 110°
to COTUB and hold.

ASOS 134.775	FAYETTEVILLE APP CON 133.0 290.25	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



4 NM Holding Pattern

CUUBE

2300 ← 313°
133° →

FEGOB

1900

3.00° TCH 45

700

4 NM

3.7 NM

1.7 NM

3000

NECIR

tr 110°

COTUB

133° to RW13

5003

5302 X 130

500

75

13

CATEGORY	A	B	C	D
LP MDA	500-1 375 (400-1)			
LNAV MDA	600-1 475 (500-1)		600-1 475 (500-1 3/8)	
CIRCLING	660-1 535 (600-1)		720-1 595 (600-1 1/2)	

MIRL Rwy 5-23 0

REIL Rwy 5 and 23 0