

WAAS CH 72908 W19B	APP CRS 191°	Rwy Idg 10801 TDZE 991 Apt Elev 1027
--	------------------------	---

RNAV (GPS) Y RWY 19R

KANSAS CITY INTL (MCI)



RNP APCH - GPS.

▼ LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. For inop ALS, increase LNAV Cats C/D visibility to RVR 5500. Simultaneous approach authorized except from SCRP and HOLMS.

ALSF-2

MISSED APPROACH: Climb to 2000 then climbing right turn to 4000 direct RUGBB and hold.

D-ATIS 128.375	KANSAS CITY APP CON 120.95 318.1	INTERNATIONAL TOWER 128.2 254.25	GND CON 121.8	CLNC DEL 135.7	CPDLC
--------------------------	--	--	-------------------------	--------------------------	-------



2000 4000 RUGBB		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 80).			
RW19R		ZESAB 1.8 NM to RW19R	PEAKA 2400	BRTNY	WESGI
0.9 NM		0.9 NM	2.5 NM	2.8 NM	5.3 NM
1600		2400	3300	5000	6000
GP 3.00°		TCH 55			
CATEGORY	A	B	C	D	
LPV DA	1191/18		200 (200-½)		
LNAV/VNAV DA	1417/40		426 (400-¾)		
LNAV MDA	1360/24	369 (400-½)		1360/35	369 (400-⅝)
CIRCLING	1540-1	513 (600-1)		1540-1½ 513 (600-1½)	1580-2 553 (600-2)