

WAAS

CH **78018**

W23A

APP CRS

229°

Rwy Idg

5000

TDZE

49

Apt Elev

53

RNAV (GPS) RWY 23


SALISBURY-OCEAN CITY WICOMICO RGNL (SBY)

RNP APCH

Baro-VNAV NA when using Georgetown altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 43°C. Rwy 23 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received use Georgetown altimeter setting: increase LPV DA to 426 feet and all Cats visibility ¼ SM; increase LNAV/VNAV DA to 503 feet; increase all MDA 60 feet and LNAV Cat C/D and Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 direct FEYKO and hold.

ASOS 118.325	PATUXENT APP CON ★ 127.95 314.0	SALISBURY TOWER ★ 119.425 (CTAF) 0	GND CON 123.775	CLNL DEL ★ 123.775	UNICOM 122.95
------------------------	---	---	---------------------------	------------------------------	-------------------------



ELEV 53

D

TDZE 49

229°

2000

FEYKO

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 45).

4 NM Holding Pattern

OKKOE

049°

229°

2000

GP 3.00° TCH 51

1700

229°

NUTPY 1700

ZASBA 1.6 NM to RW23

*LNAV only.

RW23

*600

1.6

3.4 NM

6.1 NM

CATEGORY	A	B	C	D
LPV DA	374-1		325 (400-1)	
LNAV/VNAV DA	451-1½		402 (400-1½)	
LNAV MDA	420-1		371 (400-1)	
CIRCLING	480-1 427 (500-1)	520-1 467 (500-1)	560-1½ 507 (600-1½)	700-2 647 (700-2)

REIL Rwy 5, 14 and 23 **0**
MIRL Rwy 5-23 **0**
HIRL Rwy 14-32 **0**