

WAAS CH 99436 W35A	APP CRS 354°	Rwy Idg 5506 TDZE 1155 Apt Elev 1160
--	------------------------	---

RNAV (GPS) RWY 35
STROTHER FLD (WLD)

RNP APCH.

▼ Baro-VNAV and VDP NA when using Wichita Dwight D Eisenhower Ntl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Wichita Dwight D Eisenhower Ntl altimeter setting; increase LPV DA to 1509 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 1557 feet and all visibilities ¼ SM; increase all MDA 120 feet, LNAV Cat C visibility ¾ SM and Circling Cat C visibility ¼ SM.

MISSED APPROACH:
Climb to 3600 direct
ECUWO and hold.

ASOS 118.025	KANSAS CITY CENTER 127.8 319.1	UNICOM 122.8 (CTAF) 0
------------------------	--	--


MISSED APCH FIX

4 NM

174°

354°

ECUWO



3600 ECUWO

↑

*LNAV only.

*1.4 NM to RW35

RW35

SACVY 2800

IVYIX

4 NM Holding Pattern

174° → 6000
← 354° 3000

GP 3.00°
TCH 54

1.4 NM 2.4 NM 7.0 NM

CATEGORY		A		B	C	D
LPV	DA	1405-3/4		250 (300-3/4)		NA
LNAV/ VNAV	DA	1453-1		298 (300-1)		NA
LNAV	MDA	1640-1	485 (500-1)		1640-1 3/8 485 (500-1 3/8)	NA
	CIRCLING	1680-1	520 (600-1)		1680-1 1/2 520 (600-1 1/2)	NA

